PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. §1.111 PATENT NON-FINAL

## IN THE CLAIMS:

17:20

- 1. (previously presented) A biaxially oriented film comprising a film of a polymer alloy composed of at least one of polyethylene terephthalate or poly(ethylene-2, 6-naphthalenedicarboxylate) (polymer 1) and a polyetherimide (polymer 2) as essential components, wherein micro protrusions having a height of 2 to 50 nm are formed at a density of 1,000,000 to 90,000,000/mm² on at least one surface.
- 2. (original) A biaxially oriented film according to Claim 1, wherein the number of the micro protrusions is 3,000,000 to  $60,000,000/\text{mm}^2$ .
- 3. (previously presented) A biaxially oriented film according to Claim 1, wherein the height of the micro protrusions is 2 to 30 nm.
- 4. (original) A biaxially oriented film according to Claim 1, wherein at least some of the micro protrusions are made of the polymer 1 or the polymer 2.

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. \$1.111 PATENT NON-FINAL

- 5. (original) A biaxially oriented film according to Claim 4, wherein 30% or more of the micro protrusions are made of the polymer 1 or the polymer 2.
- 6. (original) A biaxially oriented film according to Claim 1, wherein the polymer 2 has a higher glass transition temperature (Tg) than the polymer 1.
- 7. (original) A biaxially oriented film according to Claim 1, wherein the polymer 2 has compatibility with the polymer 1.

## 8-10. (canceled)

- 11. (original) A biaxially oriented film according to Claim 1, wherein the polymer 1 comprises polyethylene terephthalate.
- 12. (original) A biaxially oriented film according to Claim 1, wherein the number of the protrusions having a height of 50 nm or more is  $3000/\text{mm}^2$  or less.

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. \$1.111 PATENT NON-FINAL

- 13. (original) A biaxially oriented film according to Claim 1, wherein the number of the protrusions having a height of 30 nm or more is  $1500/\text{mm}^2$  or less.
- 14. (original) A biaxially oriented film comprising a film (A layer) according to Claim 1 laminated as at least one of outermost layers of a base layer (B layer).
- 15. (previously presented) A biaxially oriented film according to Claim 14 comprising another film (C layer) laminated as the opposite outermost layer to form a laminated structure comprising at least three layers including the A layer, the B layer and the C layer.
- 16. (previously presented) A biaxially oriented film according to Claim 15, wherein a surface roughness  $Ra_A$  on the A layer side is 0.2 to 10 nm, a surface roughness  $Ra_C$  on the C layer side is 1 to 30 nm, and  $Ra_C$  is larger than  $Ra_A$ .
- 17. (previously presented) A biaxially oriented film according to Claim 14, wherein the base layer (B layer) comprises

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. §1.111 PATENT NON-FINAL

the polymer 1 or the polymer alloy composed of the polymer 1 and the polymer 2.

- 18. (original) A biaxially oriented film according to Claim 14, wherein the number of the protrusions having a height of 50 nm or more on the A layer side surface is 3000/mm² or less.
- 19. (original) A biaxially oriented film according to Claim 14, wherein the number of the protrusions having a height of 30 nm or more on the A layer side surface is 1500/mm² or less.
- 20. (original) A biaxially oriented film according to Claim 14, wherein the content  $W_A$  (% by weight) of the polymer 2 of the A layer and the content  $W_B$  (% by weight) of the polymer 2 of the B layer satisfies the following relations:
  - $0 \le W_B \le 40$
  - $5 \le W_A \le 50$
  - $10 \le W_A W_B \le 40$
- 21. (original) A biaxially oriented film according to Claim 14, wherein the content  $W_A$  (% by weight) of the polymer 2 of

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. §1.111 PATENT NON-FINAL

the A layer and the content  $W_B$  (% by weight) of the polymer 2 of the B layer satisfies the following relations:

 $0 \le W_B \le 25$ 

17:20

02/02/2005

 $25 \le W_A \le 40$ 

 $10 \leq W_A - W_B \leq 40$ 

- 22. (original) A biaxially oriented film according to Claim 14, wherein the A layer contains substantially no inert particle.
- 23. (currently amended) A biaxially oriented film according to Claim 14, wherein the A layer contains 0.001 to 2% by weight of inert particles having an average particle diameter of  $\frac{0.01 \text{ to } 2 \text{ } \mu\text{m}}{0.01 \text{ to } 2 \text{ } \mu\text{m}}$ .
- 24. (currently amended) A biaxially oriented film according to Claim 23, wherein the A layer contains 0.01 to 1% by weight of inert particles having an average particle diameter of  $\frac{0.01 \text{ to } 1 \text{ mm}}{0.01 \text{ to } 1 \text{ mm}}$ .
- 25. (original) A biaxially oriented film comprising a laminated structure of at least three layers including A layer, B

6

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. \$1.111

PATENT NON-FINAL

layer and C layer, wherein the A layer comprises a film composed of polyester and polyetherimide and has a surface roughness  $Ra_A$  of 0.2 to 10 nm, and the layer opposite to the A layer has a surface roughness  $Ra_C$  is 1 to 30 nm.

- 26. (original) A biaxially oriented film according to Claim 25, wherein the surface roughness  $Ra_{\rm A}$  of the A layer is 0.5 to 5 nm, the surface roughness  $Ra_{\rm C}$  of the layer opposite to the A layer is 5 to 15 nm, and  $Ra_{\rm C}$  is larger than  $Ra_{\rm A}$ .
- 27. (previously presented) A magnetic recording medium comprising a biaxially oriented film according to Claim 1, and a magnetic layer provided on one side of the biaxially oriented film.
- 28. (original) A magnetic recording medium according to Claim 27, wherein the magnetic layer comprises a ferromagnetic metal thin film.
- 29. (original) A magnetic recording medium according to Claim 27, wherein the magnetic layer comprises a ferromagnetic metal fine powder dispersed in a binder.

PATENT APPLN. NO. 09/830,215 RESPONSE UNDER 37 C.F.R. §1.111

17:20

02/02/2005

PATENT NON-FINAL

- 30. (previously presented) A biaxially oriented film according to Claim 2, wherein the height of the micro protrusions is 2 to 30 nm.
- 31. (previously presented) A biaxially oriented film according to Claim 15, wherein the C layer comprises a polyester.
- 32. (previously presented) A biaxially oriented film according to Claim 15, wherein the C layer comprises the same polymer as the B layer.